## (19) World Intellectual Property Organization International Bureau





### (43) International Publication Date 11 December 2003 (11.12.2003)

### **PCT**

# (10) International Publication Number WO 03/102905 A1

(51) International Patent Classification<sup>7</sup>: G02F 1/133

G09G 3/20,

(21) International Application Number: PCT/IB03/02234

(22) International Filing Date: 21 May 2003 (21.05.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data: 0212566.4

31 May 2002 (31.05.2002) GH

(71) Applicant (for all designated States except US): KONIN-KLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).

(72) Inventor; and

(75) Inventor/Applicant (for US only): BATTERSBY, Stephen, J. [GB/GB]; c/o Philips Intellectual Property & Standards, Cross Oak Lane, Redhill, Surrey RH1 5HA (GB).

(74) Agent: SHARROCK, Daniel, J.; Philips Intellectual Property & Standards, Cross Oak Lane, Redhill, Surrey RH1 5HA (GB).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

#### Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: NON RECTANGULAR DISPLAY DEVICE



(57) Abstract: A display device has an array 40 of pixels and row and column driver circuitry comprising row driver circuit portions R and column driver circuit portions C, each pixel being addressed by a row driver circuit portion R and a column driver circuit portion C which connect to respective row and column conductor lines. The array of pixels has a non-rectangular outer shape, and the device comprises at least three row driver circuit portions R and at least three column driver circuit portions C disposed alternately around the outer periphery of the array. This arrangement enables row and column drivers to be divided into portions which are arranged in such a way that addressing can be provided for complicated display shapes.

WO 03/102905 A1